



HRQ versione B

Models		0524	0604	0704	0804	0904	1004
COOLING ONLY							
Cooling capacity(1)	kW	131	148	168	197	222	240
Total power input(1)	kW	56,3	65,3	79,2	91,5	99,8	111
EER		2,33	2,27	2,12	2,15	2,22	2,16
ESEER		*	*	*	*	*	*
HEATING ONLY							
Heating capacity(2)	kW	144	167	190	219	245	266
Total power input(2)	kW	55,2	62,8	71,7	85,0	93,0	100
COP		2,61	2,66	2,65	2,58	2,63	2,66
COMPRESSORS							
No. Compressors/No. Circuits	N.	4/2	4/2	4/2	4/2	4/2	4/2
FANS							
Fan air flow	m ³ /h	54000	54000	54000	72000	72000	72000
Maximum useful static pressure(3)	Pa	120	120	120	120	120	120
NOISE LEVELS							
Sound power(3)	dB(A)	100	100	100	101	101	101
SIZE							
A	mm	3602	3602	3602	4602	4602	4602
B	mm	1277	1277	1277	1277	1277	1277
H	mm	1925	1925	1900	2235	2235	2235
Operating weight	kg.	1800	1910	2095	2735	2855	2895

Data referred to:

1 Evaporator water (in/out): 12/7°C; Condenser air (in): 35°C.

2 Condenser water (in/out): 40/45°C; evaporator air (in): 7°C - r.h. 87%.

3 Sound pressure in open field conditions on reflecting surface (directivity factor Q=2), average value on longest side, at 1 m from the outer surface and at 1 m height in relation to the unit supporting base.

* Please contact our sales department

Minimum clearance required

		0524 - 1004
Switchboard side	mm	800
Switchboard opposite side	mm	800
Condensation coil side	mm	1000

