



## HRD

Models		0021	0031	0051	0071	0091	0101	0121	0151
<b>Indoor Unit</b>									
Air flow Max	m3/h	290	600	1000	1400	1900	2500	3200	4000
Sound Level Max(1)	dB(A)	54	56	54	59,5	58	57,5	60,5	62
Axle power available	W	2x45	2x90	2x147	2x350	2x350	2x350	2x550	2x750
Poles	N°	4	2	4	4	4	4	4	4
Max. absorption	A	1,3	1,8	3,0	5,8	6,2	6,0	11,4	6,2
N° fan speeds	N°	2	1	3	3	3	3	3	2
Efficiency	%	52,3	54,6	53,4	52,1	51,8	57,6	56,0	55,6
Recuperated thermal power	kW	1	3	5	6	8	12	15	19
Renewal air temperature	°C	8,10	8,70	8,30	8,00	7,90	9,40	9,00	8,90
Efficiency		G3	G3	G3	G3	G3	G3	G3	G3
Frontal air speed	m/s	1,7	3,6	2,9	4,1	4,5	3,8	4,3	4,3
Protection grade	IP	20	54	44	55	44	55	20	55
Isolation grade		B	F	F	F	F	F	F	F
ESP	Pa	40	80	90	140	120	110	170	170
Electrical power supply internal unit	V-Ph-Hz	230V~50Hz	230V~50Hz	230V~50Hz	230V~50Hz	230V~50Hz	230V~50Hz	230V~50Hz	
<b>Dimension</b>									
Internal Unit									
L	mm	990	990	1150	1350	1450	1700	1700	1700
H	mm	750	750	860	900	900	1230	1230	1230
P	mm	270	270	385	410	470	490	530	630
Net weight	kg	39	41	68	91	99	140	155	179

Data referred to

1 Sound pressure measured at 1 m in open field conditions

Dimension

